



US009409601B2

(12) **United States Patent**
Hoiss

(10) **Patent No.:** **US 9,409,601 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **MOTOR VEHICLE HAVING AN AXLE SUPPORT**

(56) **References Cited**

(71) Applicant: **Bayerische Motoren Werke Aktiengesellschaft**, Munich (DE)

(72) Inventor: **Franz Hoiss**, Bernried (DE)

(73) Assignee: **Bayerische Motoren Werke Aktiengesellschaft**, Munich (DE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/737,881**

(22) Filed: **Jun. 12, 2015**

(65) **Prior Publication Data**

US 2015/0274210 A1 Oct. 1, 2015

Related U.S. Application Data

(63) Continuation of application No. PCT/EP2013/075953, filed on Dec. 9, 2013.

(30) **Foreign Application Priority Data**

Dec. 14, 2012 (DE) 10 2012 223 292

(51) **Int. Cl.**

B62D 21/11 (2006.01)

B62D 21/15 (2006.01)

B62D 25/08 (2006.01)

B60K 5/12 (2006.01)

(52) **U.S. Cl.**

CPC **B62D 21/155** (2013.01); **B60K 5/12** (2013.01); **B62D 25/085** (2013.01)

(58) **Field of Classification Search**

CPC **B62D 21/11**; **B62D 21/155**; **B62D 25/085**; **B60K 5/12**

See application file for complete search history.

U.S. PATENT DOCUMENTS

5,605,353 A * 2/1997 Moss B62D 21/09 188/376

5,740,876 A * 4/1998 Shimose B60K 5/1216 180/232

5,884,963 A 3/1999 Esposito et al.

(Continued)

FOREIGN PATENT DOCUMENTS

AT 005 453 U1 7/2002
CA 2 236 816 C 8/2002

(Continued)

OTHER PUBLICATIONS

International Search Report (PCT/ISA/210) dated Feb. 27, 2014, with English Translation (four (4) pages).

(Continued)

Primary Examiner — Laura Freedman

(74) *Attorney, Agent, or Firm* — Crowell & Moring LLP

(57) **ABSTRACT**

A rear region of an axle support is connected to at least one supporting body component in the front, lower region of the passenger compartment of the vehicle body by way of at least one support extending rearward. The support is connected to the supporting body component by a pyrotechnically releasable connecting element. A guide is arranged between the rear end region of the support and the supporting body component, which guide permits only an displacement of the guided end region of the support rearward as viewed in the direction of travel if the connection is released by the pyrotechnic connecting element between the support and the supporting body component.

13 Claims, 2 Drawing Sheets

